

PS-DIN Power Supply

Power supplies for DIN rail mounting

- Compact design
- Easy to connect
- For DIN rail mounting



Technical data

General properties

dimensions All dimensions are width x height x depth

Product variants

PS-DIN-AC/12/20

U-IN: 85-264VAC, 120-370VDC
 U-OUT: 12VDC
 P: 20W
 22,5 x 90 x 100mm
 T: -20°C ... +70°C

PS-DIN-AC/24/20

U-IN: 85-264VAC, 120-370VDC
 U-OUT: 24VDC
 P: 20W
 22,5 x 90 x 100mm
 T: -20°C ... +70°C

PS-DIN-AC/24/40

U-IN: 85-264VAC, 120-370VDC
 U-OUT: 24VDC
 P: 40W
 40 x 90 x 100mm
 T: -20°C ... +70°C



PS-DIN-AC/24/240 U-IN: 90-264VAC, 127-370VDC
U-OUT: 24-27VDC
P: 240W
125 x 114 x 63mm
T: -20°C ... +70°C

PS-DIN-AC/48/40 U-IN: 85-264VAC, 120-370VDC
U-OUT: 48-56VDC
P: 40W
40 x 90 x 100mm
T: -20°C ... +70°C

PS-DIN-AC/48/60 U-IN: 85-264VAC, 120-370VDC
U-OUT: 48-56VDC
P: 60W
40 x 90 x 100mm
T: -20°C ... +70°C

PS-DIN-AC/48/100 U-IN: 88-264VAC, 124-370VDC
U-OUT: 48-56VDC
P: 100W
55 x 90 x 100mm
T: -10°C ... +60°C

PS-DIN-AC/48/120 U-IN: 88-264VAC, 124-370VDC
U-OUT: 48-53VDC
P: 120W
40 x 125 x 114mm
T: -25°C ... +70°C

PS-DIN-AC/48/240 U-IN: 90-264VAC, 123-370VDC
U-OUT: 48-55VDC
P: 240W
63 x 125 x 114mm
T: -25°C ... +75°C

PS-DIN-AC/48/480 U-IN: 180-264VAC, 250-370VDC
U-OUT: 48-55VDC
P: 480W
230 x 125 x 129mm
T: -20°C ... +70°C

PS-DIN-AC/48/480/k U-IN: 90-264VAC, 127-370VDC
U-OUT: 48-53VDC
P: 480W
86 x 125 x 130mm
T: -25°C ... +70°C

Version 27.10.2022, Changes without notice