

PS-DIN Power Supply

Power supplies for DIN rail mounting

- Compact design
- Easy to connect
- For DIN rail mounting



Technical data

General properties

dimensions All dimensions are width x height x depth

Product variants

PS-DIN-AC/12/20
 U-IN: 85-264VAC, 120-370VDC
 U-OUT: 12VDC
 P: 20W
 22,5 x 90 x 100mm
 T: -20°C ... +70°C

PS-DIN-AC/24/20
 U-IN: 85-264VAC, 120-370VDC
 U-OUT: 24VDC
 P: 20W
 22,5 x 90 x 100mm
 T: -20°C ... +70°C

PS-DIN-AC/24/40
 U-IN: 85-264VAC, 120-370VDC
 U-OUT: 24VDC
 P: 40W
 40 x 90 x 100mm
 T: -20°C ... +70°C



PS-DIN-AC/48/40	U-IN: 85-264VAC, 120-370VDC U-OUT: 48-56VDC P: 40W 40 x 90 x 100mm T: -20°C ... +70°C
PS-DIN-AC/48/60	U-IN: 85-264VAC, 120-370VDC U-OUT: 48-56VDC P: 60W 40 x 90 x 100mm T: -20°C ... +70°C
PS-DIN-AC/48/100	U-IN: 88-264VAC, 124-370VDC U-OUT: 48-56VDC P: 100W 55 x 90 x 100mm T: -10°C ... +60°C
PS-DIN-AC/48/120	U-IN: 88-264VAC, 124-370VDC U-OUT: 48-53VDC P: 120W 40 x 125 x 114mm T: -25°C ... +70°C
PS-DIN-AC/48/120SK	U-IN: 176-264VAC, 254-370VDC U-OUT: 48-55VDC (alarm contact) P: 120W 66 x 125 x 114mm T: -25°C ... +60°C
PS-DIN-AC/48/240	U-IN: 90-264VAC, 123-370VDC U-OUT: 48-55VDC P: 240W 63 x 125 x 114mm T: -25°C ... +75°C
PS-DIN-AC/48/480	U-IN: 180-264VAC, 250-370VDC U-OUT: 48-55VDC P: 480W 230 x 125 x 129mm T: -20°C ... +70°C
PS-DIN-AC/48/480/k	U-IN: 90-264VAC, 127-370VDC U-OUT: 48-53VDC P: 480W 86 x 125 x 130mm T: -25°C ... +70°C

Version 24.09.2018, Changes without notice