

RY-LGSP23-26/370

19"-L2/L3 Switch with management, 24 Ports
PoE +

- 19" L2/L3 Switch with PoE+ 370W
- Copper ports: 26 x 10/100/1000TX with PoE+
- Optical fibre ports: 2x100/1000Mbit/s (Combo)
- With management, ring-capable, L3 functions, DMS
- Supply voltage 230VAC



Being developed for tasks with high data volume, this layer 2/3 switch with L3 functions is suitable for example for video over IP and video streaming in connection with multicast as well. IP-cameras are supplied by PoE through the data cable. Its compact design and reduced number of ports make this switch ideal for smaller plants or as a remote unit in a larger network. With its extensive management possibilities, it is also suitable for complex network structures.

Video network special features

Video-friendly features

Extra high backplane performance for a smooth video transmission with all ports assigned. Support of Jumbo Frames up to 9600Bytes by 100Mbit/s. MAC-address restriction ensures port security.

Active monitoring of the camera

Switch-powered cameras by PoE are constantly monitored. In case of a camera failure the switch automatically restarts the camera. If this is not possible the switch alarms by SNMP.

Active monitoring PoE-supply

The switch alarms by SNMP in case of sudden excessive power consumption by a defect camera for example.

Active management of the PoE-performance

The PoE-ports can be started by time intervals so as to prevent an overload of the PoE power supplies.

DMS



This switch disposes of an integrated network monitoring and control system which gives the user a good overview over the whole network in an easy way. This DMS-system has the following qualities:

Graphical network map

The network map gives a quick overview over all switches and terminal devices such as IP-cameras or servers indicating the IP-address, type of device and equipment. Plans and maps can be saved as background pictures and thus enable the user to access to certain devices without knowledge of the entire IP-structure.

Device search

This function enables the access to a specific device also in large networks. Recently added devices, as per example a new IP-camera, are immediately displayed and thus enable a direct access.

Data traffic display

Graphical display of data traffic per port in a time axis.

Error handling and security

Network diagnosis between master switch and terminal devices. Protective mechanisms such as data flow restriction guarantee an effective protection against inadvertent access. IEEE802.3ah and IEEE802.1ag provide tools for structuring of networks.

Technical data

General properties

supply voltage	100-240VAC, 50-60Hz
power consumption	Max. 40W (without PoE) / 255W (with PoE 185W) / 450W (with PoE 370W)
MTBF	25°C: 336'970h 40°C: 185'371h
operating temperature	0°C to 40°C
dimensions	442 x 211 x 44mm (Width x Depth x Height)

interfaces

copper ports	26 x 10/100/1000TX, RJ45, therefrom 24 with PoE+ 802.3af/at Maximum PoE for all ports: 370W
optical fibre ports	2 x 100/1000, SFP (Combo) We recommend the use of our barox SFPs. We do not test or guarantee the compatibility of our devices with SFPs of other manufacturers.
console port	RS232, RJ45



network properties

backplane	52Gbit/s
MAC-table	8k
configuration	Console, Web GUI, SNMPv1, v2c and v3
PoE Management	
port settings	Port disable/enable. Auto-negotiation 10/100/1000Mbps. Flow Control disable/enable. Data rate control on every port. Max. framesize, power control
port status	Display per port: Speed link status, flow control status. Auto negotiation status, trunk status.
layer3 functions	IPv4 and IPv6 Unicast: static routing
VLAN	802.1Q Tagged based VLAN, up to 255 VLAN-groups, Q-in-Q, private VLAN
link aggregation	IEEE 802.3ad LACP / static trunk, supports 18 groups of 8-port trunks or static trunk
QoS	Traffic classification based, strict priority and WRR, 4-level priority for switching - Port number - 802.1p priority - DS/TOS field in IP package
security	SSH v1 and v2, SSL, 802.1X RADIUS, port security, ACL with MAC, IP, Multicast etc. User authentication with private key
multicast	IGMP v1/v2/v3 snooping, up to 1024 multicast groups, source-specific multicast, IGMP Proxy
topology	STP, RSTP, MSTP



standards

IEEE 802.3 10Base-T
IEEE 802.3u 100Base-TX/100BASE-FX
IEEE 802.3z Gigabit SX/LX
IEEE 802.3ab Gigabit 1000T
IEEE 802.3x Flow Control and Back pressure
IEEE 802.3ad Port trunk with LACP
IEEE 802.1d Spanning tree protocol
IEEE 802.1w Rapid spanning tree protocol
IEEE 802.1s Multiple spanning tree protocol
IEEE 802.1p Class of service
IEEE 802.1Q VLAN Tagging
IEEE 802.1x Port Authentication Network Control
IEEE 802.1ab LLDP
IEEE 802.3af/at Power over Ethernet
IEEE 802.az Energy Efficient Ethernet



Product variants

RY-LGSP23-26

Switch with 185W for PoE

RY-LGSP23-26/370

Switch with 370W for PoE

Version 18.11.2023, Changes without notice