

## VI-3005

PoE-switch with uplink by UTP or LWL

- Switch IP/PoE with UPT- and LWP Uplink
- Supplied by PoE
- PoE 802-1 af and et
- 4 ports and one uplink ports



With this switch VI-3005 four ethernet ports 10/100BaseTX with uplink can be connected with an uplink by UTP or LWL cable. The switch can either supply the electrical consumers directly by PoE or it can be powered by the uplink-port with PoE itself. Thanks to a time-saving "plug-and-play" there is no software configuration needed. VI-3005 is small and thus widely applicable.

### More information

---

Special features	Ethernet: Compatible with several network protocols incl. IEEE802.3, 802.3u, 802.3x Supports Jumbo Frames up to 9kB Tag transparent
------------------	--



## Technical data

---

### General properties

supply voltage	By uplink-Port RJ 45 with max. 60W or 48-57VDC Without PoE: 12VDC
MTBF	
operating temperature	-30°C to +75°C
dimensions	115 x 80 x 30mm (Width x Length x Height) BXL: Base plate without plug
weight	0,2kg

### interfaces

copper ports	4 x 10/100BaseT Ethernet with PoE 801.3af and at, RJ45
uplink ports	1 x 10/100BaseT, RJ45 1 x SFP slot, currently only fits with VI-SFP-MMA-H, 100MBit/s, 2 fibres multimode, 2km

## Product variants

---

<b>VI-3005</b>	VI-3005 front view Excl. power supplies, excl. SFP
<b>VI-3005</b>	VI-3005 back view
<b>VI-SFP-MMA-H</b>	To be ordered separately: SFP only compatible with the VI-3005 switch Data rate 100MBit/s 2 fibres multimode, max. 2km Connector LC-Duplex

Version 12.05.2021, Changes without notice