



PS-DIN Power Supply

Power supplies for DIN rail mounting

- Compact design
- Easy to connect
- For DIN rail mounting



Technical data

General properties

MTBF

dimensions

All dimensions are width x height x depth

Product variants

PS-DIN-AC/12/20	U-IN: 85-264VAC, 120-370VDC U-OUT: 12VDC P: 20W 22,5 x 90 x 100mm T: -20°C ... +70°C
PS-DIN-AC/24/20	U-IN: 85-264VAC, 120-370VDC U-OUT: 24VDC P: 20W 22,5 x 90 x 100mm T: -20°C ... +70°C
PS-DIN-AC/24/40	U-IN: 85-264VAC, 120-370VDC U-OUT: 24VDC P: 40W 40 x 90 x 100mm T: -20°C ... +70°C



PS-DIN-AC/24/240	U-IN: 90-264VAC, 127-370VDC U-OUT: 24-27VDC P: 240W 125 x 114 x 63mm T: -20°C ... +70°C
PS-DIN-AC/48/40	U-IN: 85-264VAC, 120-370VDC U-OUT: 48-56VDC P: 40W 40 x 90 x 100mm T: -20°C ... +70°C
PS-DIN-AC/48/60	U-IN: 85-264VAC, 120-370VDC U-OUT: 48-56VDC P: 60W 40 x 90 x 100mm T: -20°C ... +70°C
PS-DIN-AC/48/100	U-IN: 88-264VAC, 124-370VDC U-OUT: 48-56VDC P: 100W 55 x 90 x 100mm T: -10°C ... +60°C
PS-DIN-AC/48/120	U-IN: 88-264VAC, 124-370VDC U-OUT: 48-53VDC P: 120W 40 x 125 x 114mm T: -25°C ... +70°C
PS-DIN-AC/48/240	U-IN: 90-264VAC, 123-370VDC U-OUT: 48-55VDC P: 240W 63 x 125 x 114mm T: -25°C ... +75°C
PS-DIN-AC/48/480	U-IN: 180-264VAC, 250-370VDC U-OUT: 48-55VDC P: 480W 230 x 125 x 129mm T: -20°C ... +70°C
PS-DIN-AC/48/480/k	U-IN: 90-264VAC, 127-370VDC U-OUT: 48-53VDC P: 480W 86 x 125 x 130mm T: -25°C ... +70°C

Version 27.10.2022, Changes without notice